

## Towing Tractor QCF series

- Strong power.
- Modern styling with innovative design elements.
- Ergonomically designed spacious and comfortable cabin.
- Well-located instrument panel for easy viewing & Conveniently controlled driving system.
- Imported edition binding power and gearing parts realize synchronized or stepless shifting, and provide the excellent performance.
- The dual stages towing hitch operates easily.
- ▲ The whole power steering ensures steady and safe control of the tractor.



	Power type		Diesel		
	i-Lift No.			1810801	1810802
Model				QCF200	QCF250
o	Max. drawbar pull		KN	20	25
	Max. towed weight at dry even concrete surface	With one trailer	Kg	26000	33000
nar		With a train of trailers		39000	49000
Performance	Max. travel speed	Forward	Km/h	26	
		Backward		23	
	Max. gradeability (without load)		%	38	
	Overall length (with coupler)			3085	
	Overall width			1440	
	Overall height			1440	
	Wheelbase			1600	
Dimensions	Front overhang			640	
	Rear overhang(with coupler)		mm	845	
	Front tread			1230	
	Rear tread			1190	
	Min. turning radius (outer)			3265	
	Floor height			425	
	Seat height I			980	
	Center height coupler I			350/450	
	Min. ground clearance M			130	
Ë	Truck weight			3550	4050
Weight	Weight distribution	Front axle	Kg	1100	1080
		Rear axle		2450	2970
Tyre	Front tyre			650-10-10PR	
	Rear tyre			700-15-12PR	
Engine	Model		L	NISSAN TD27	
	Displacement		сс	2663	
	Rated output		Kw/rpm	44.1/2400	
	Rated torque		N-m/rpm	172/1600	