

Flexible Conveyor PR / SR / FWB series

- ▲ Provide flexible mobile handling facilities.
- ▲ Move goods quickly, safely and efficiently, then close for storage.
- ▲ Versatile conveyor system that can be expanded to suit most locations.
- ▲ Height adjustable range: a. 700-900mm b. 800-1000mm c. 900-1150mm
- ▲ Pitch: Closed 32mm, extended 150mm.



PR5626



FWB3852

i-Lift No.	Plastic Wheel	2510101	2510102	2510103	2510104	2510105	2510106
	Steel Wheel	2510113	2510114	2510115	2510116	2510117	2510118
Model	Plastic Wheel	PR4313	PR4417	PR4522	PR4626	PR5313	PR5417
	Steel Wheel	SR4313	SR4417	SR4522	SR4626	SR5313	SR5417
Capacity	kg(lb.)	210(462)	280(616)	350(770)	420(924)	210(462)	280(616)
Track Width	mm(in.)	450(17.7)				500(20)	
Wheel Per Spindle		6					
No. of Section		3	4	5	6	3	4
Length closed/extended ^a	mm(in.)	1068-3642(42-143.4)	1368-4734(54-186.4)	1668-5826(65.7-229)	1968-6918(77.5-272)	1068-3642(42-143.4)	1368-4734(54-186.4)
Loading	kg(lb.)/section	70(154)					

i-Lift No.	Plastic Wheel	2510107	2510108	2510109	2510110	2510111	2510112
	Steel Wheel	2510119	2510120	2510121	2510122	2510123	2510124
Model	Plastic Wheel	PR5522	PR5626	PR6313	PR6417	PR6522	PR6626
	Steel Wheel	SR5522	SR5626	SR6313	SR6417	SR6522	SR6626
Capacity	kg(lb.)	350(770)	420(924)	210(462)	280(616)	350(770)	420(924)
Track Width	mm(in.)	500(20)		600(23.6)			
Wheel Per Spindle		6			8		
No. of Section		5	6	3	4	5	6
Length closed/extended ^a	mm(in.)	1668-5826(65.7-229)	1968-6918(77.5-272)	1068-3642(42-143.4)	1368-4734(54-186.4)	1668-5826(65.7-229)	1968-6918(77.5-272)
Loading	kg(lb.)/section	70(154)					

i-Lift No.	2510130	2510131	2510132	2510133	2510134	2510135	2510136	2510137	2510138	2510139
Model	FWB3852	FWB3853	FWB3854	FWB3855	FWB3856	FWB3862	FWB3863	FWB3864	FWB3865	FWB3866
Capacity	kg(lb.)	100(220)	150(330)	200(440)	250(550)	300(660)	100(220)	150(330)	200(440)	250(550)
Track Width	mm(in.)	500(20)					600(23.6)			
Wheel Per Spindle		3	4	5	6	7	3	4	5	6
No. of Section		2	3	4	5	6	2	3	4	5
Length closed/extended ^a	mm(in.)	940-2350 (37-92.5)	1320-3350 (52-131.9)	1700-4350 (67-171.3)	2080-5350 (81.9-210)	2460-6350 (96.8-250)	940-2350 (37-92.5)	1320-3350 (52-131.9)	1700-4350 (67-171.3)	2080-5350 (81.9-210)
Loading	kg(lb.)/section	50(110)								