

Steel Jack HVS/HKB series

- i-LIFT steel jacks HVS and HKB are developed in accordance with the latest safety regulations. With milled rack, geared wheels and tempered parts of driving gear.
- In accordance with DIN 7355 (type HVS).
- Suitable for lifting loads of any type.
- With lifting body.
- Safety crank with folding handle.
- Type HKB comes with low body height.
- Lifting either with fixed toe or on clawed head.
- All construction components standardized.
- Low expenditure of force through optimal ratio.



HVS-10

i-Lift No.		2310101	2310102	2310103	2310104	2310105	2310106	2310107	2310108	2310109
Model		HVS-1.5	HVS-3	HVS-5	HVS-10	HVS-20	HKB-1.5	HKB-3	HKB-5	HKB-10
Safe Working Load	kg(lb.)	1500(3300)	3000(6600)	5000(11000)	10000(22000)	20000(44000)	1500(3300)	3000(6600)	5000(11000)	10000(22000)
Height of Load	mm(in.)	725(28.5)			800(31.5)		570(22.4)		600(23.6)	650(25.6)
Lifting Height	mm(in.)	350(13.8)		300(12)		340(13.4)	300(12)			
Height of Claw In Lowest Position	mm(in.)	70(2.8)	75(3)	70(2.8)	90(3.5)	95(3.7)	70(2.8)	75(3)	70(2.8)	80(3.1)
Net Weight	kg(lb.)	12(26.4)	20(44)	24(52.8)	42(92.4)	60(132)	11(24.2)	18(39.6)	22(48.4)	38(83.6)

Steel Jack HAS series

with adjustable lifting claw

- Suitable for lifting loads of any type
- For a variety of lifting points
- Low expenditure of force through optimal ratio
- Lifting claw adjustable in 6 positions
- Large base plate

i-Lift No.		2310201	2310202	2310203	2310204
Model		HAS-3	HAS-5	HAS-10	HAS-15
Safe Working Load	kg(lb.)	3000(6600)	5000(11000)	10000(22000)	15000(33000)
Height of Load	mm(in.)	720(28.3)		792(31.6)	805(31.7)
Lifting Height	mm(in.)	350(13.8)	300(12)		285(11.2)
Height of Claw In Lowest Position	mm(in.)	69(2.7)	64(2.5)	85(3.3)	120(4.7)
Net Weight	kg(lb.)	25(55)	30(66)	48(105.6)	63(138.6)



HAS-10

Safety Ratchet Crank T series

To be supplied as an option for steel jacks

i-Lift No.		2310301	2310302
Model		T250	T300
Suitable for use with	kg(lb.)	1500 to 5000(3300 to 11000) steel jacks	10000 to 20000(22000 to 44000) steel jacks
Arm Length	mm(in.)	250(10)	300(12)
Handle Length	mm(in.)	130(5.1)	250(10)



T300

T250