

## Forklift Jack HFJ serie

### HFJ-400 / HFJ-700A

- High capacity and rugged construction.
- Extra low pick up point and 2-position lift pad for hard-to reach places under low profile lift trucks.
- Specially designed hydraulic pump with German seal kits and overload valve.
- Removable handle and compact size.
- **Conforms to CE standard and ANSI standard.**

### HFJ-500

- **Uniquely built in two lifting speeds.**  
Quick lifting and slow lifting which can be automatically switched between with load and without load.  
Quick lifting: 20 times pump strokes.  
Slow lifting: 60 times pump strokes.
- **Two alternative lifting positions.**  
Low position: capacity 4000kg.  
High position: capacity 5000kg.
- **Built in overload valve and bypass valve.**  
Guarantees safety and reliable operation.
- **Low profile lifting: 65mm.**



i-Lift No.	2310601	2310602	2310603	
Model	HFJ-400	HFJ-700A	HFJ-500	
Lifting Position	--	--	Low position	High position
Rated Capacity	kg(lb.) 4000(8800)	7000(15400)	4000(8800)	5000(11000)
Min. Lifting Height	mm(in.) 65(2.5)	65(2.5)	65(2.5)	414(16.3)
Max. Lifting Height	mm(in.) 406(16)	420(16.5)	425(16.7)	720(28.3)
Width	mm(in.) 203(8)	250(10)	210(8.3)	
Pump Stroke to Max. Height	45	45	60	
Packing Size	mm(in.) 700x240x460(27.5x9.5x18)	780x290x520(30.7x11.4x20.5)	720x260x350(28.3x10.2x13.8)	
Net Weight	kg(lb.) 33(73)	48(106)	45(99)	
Gross Weight	kg(lb.) 35(77)	51(112)	47(103)	

## Forklift Support Stand HT series

- Heavy duty design and wide base.
- Heat treated heavy-duty holding pins.
- Provide support for forklifts or heavy machinery.



i-Lift No.	2310702	2310703
Model	HT-7	HT-9
Used with Forklift Jack	HFJ-400A	HFJ-700A
Capacity/Pair	kg(lb.) 14000(30800)	18000(39600)
Adjustable Range	mm(in.) 242-400(9.5-16)	242-415(9.5-16.3)
Net Weight	kg(lb.) 13(28.6)	15(33)

**Note:** Sold in pairs only

