

Cargo Lashing

- i-LIFT cargo-lashings are produced from high tenacity polyester yarns.
- Low-strain, wear-resistant, long-life strap material (100% polyester).
- Various end fittings are available to suit specific lashing needs.
- In accordance with DIN 60060 and pr-EN 12195-2.

For Europe

Type							
i-lift No.			2313801	2313802	2313803	2313804	2313805
Model			R2035A	R2035B	R2035C	R2035D	R4035N
	Load Capacity System	(daN)	2000				4000
	Load Capacity System	(daN)	1000				2000
	Breaking Strength Webbing	(daN)	3000				
	Webbing Width	(mm)	35				
	End Fitting		Grab hook	One top grab hook	Claw hook	Twisted snap hood	Endless

Fixed end: 0.5m. Standard length: R2050A to 2050E 6m, R4050N 6m(Endless)

Type							
i-lift No.			2313806	2313807	2313808	2313809	2313810
Model			R4050A	R4050B	R4050C	R4050D	R4050E
	Load Capacity System	(daN)	4000				8000
	Load Capacity System	(daN)	2000				4000
	Breaking Strength Webbing	(daN)	6000				
	Webbing Width	(mm)	50				
	End Fitting		Grab hook	One top grab hook	Claw hook	Twisted snap hook	Hook with safety latch

Fixed end: 0.5m. Standard length: R4050A to 4050E 8m, R8050N 6m(Endless)

Type							
i-lift No.			2313812	2313813	2313814	2313815	2313816
Model			R5050A	R5050B	R5050C	R5050D	R5050E
	Load Capacity System	(daN)	5000				10000
	Load Capacity System	(daN)	2500				5000
	Breaking Strength Webbing	(daN)	7500				
	Webbing Width	(mm)	50				
	End Fitting		Grab hook	One top grab hook	Claw hook	Twisted snap hook	Hook with safety latch

Fixed end: 0.5m. Standard length: R5050A to 5050E 8m, R10050N 6m(Endless). 9m and 10m available.

