

Flat Webbing Sling W25 series

- i-LIFT flat webbing slings are made from high tensile polyester (PES).
- Manufactured according to machine directive 89/392/CE and DIN61360.
- Low elongation.
- Color coded according to DIN-EN1492-1.
- Each 25mm webbing width is equal to 1 tonne capacity.
- UV-resistant, eliminating material aging or embrittlement.
- Moisture-resistant fabric, thus preventing frost damage (up to approx.-40°C).

For Europe



W25-3

i-lift No.				2314101	2314102	2314103	2314104	2314105	2314106	
Model				W25-1	W25-2	W25-3	W25-4	W25-5	W25-6	
Webbing Width			(mm)	25	50	75	100	125	150	
Colour Coded According to DIN-EN1492-1				WLL 1T	WLL 2T	WLL 3T	WLL 4T	WLL 5T	WLL 6T	
Working Load Limit with 1 Webbing Sling	Straight Lift			1,0	1.000	2.000	3.000	4.000	5.000	6.000
	Chocked Lift			0,8	800	1.600	2.400	3.200	4.000	4.800
	β	0-7°		2,0	2.000	4.000	6.000	8.000	10.000	12.000
		7°-45°		1,4	1.400	2.800	4.200	5.600	7.000	8.400
		45°-60°		1,0	1.000	2.000	3.000	4.000	5.000	6.000
Working Load Limit with 2 Webbing Sling	Straight Lift up to 45°			1,4	1.400	2.800	4.200	5.600	7.000	8.400
	Chocked Lift up to 45°			1,12	1.120	2.240	3.360	4.480	5.600	6.720
	Straight Lift 45°-60°			1,0	1.000	2.000	3.000	4.000	5.000	6.000
	ChockedLift 45°-60°			0,8	800	1.600	2.400	3.200	4.000	4.800

Usual length 1m, 1.5m, 2m, 2.5m, 3m, 4m, 5m, 6m, 7m, 8m, 10m

Flat Webbing Sling W30 series

- i-LIFT flat webbing slings are made from high tensile polyester (PES).
- Manufactured according to machine directive 89/392/CE and DIN61360.
- Low elongation.
- Color coded according to DIN-EN1492-1.
- Each 30mm webbing width is equal to 1 tonne capacity.
- UV-resistant, eliminating material aging or embrittlement.
- Moisture-resistant fabric, thus preventing frost damage (up to approx.-40°C).

For Europe



W30-3

i-lift No.				2314201	2314202	2314203	2314204	2314205	
Model				W30-1	W30-2	W30-3	W30-4	W30-5	
Webbing Width			(mm)	30	60	90	120	150	
Colour Coded According to DIN-EN1492-1				WLL 1T	WLL 2T	WLL 3T	WLL 4T	WLL 5T	
Working Load Limit with 1 Webbing Sling	Straight Lift			1,0	1.000	2.000	3.000	4.000	5.000
	Chocked Lift			0,8	800	1.600	2.400	3.200	4.000
	β	0-7°		2,0	2.000	4.000	6.000	8.000	10.000
		7°-45°		1,0	1.000	2.000	3.000	4.000	5.000
		45°-60°		0,7	700	1.400	2.100	2.800	3.500
Working Load Limit with 2 Webbing Sling	Straight Lift up to 45°			1,4	1.400	2.800	4.200	5.600	7.000
	Chocked Lift up to 45°			1,12	1.120	2.240	3.360	4.480	5.600
	Straight Lift 45°-60°			1,0	1.000	2.000	3.000	4.000	5.000
	ChockedLift 45°-60°			0,8	800	1.600	2.400	3.200	4.000

Usual length 1m, 1.5m, 2m, 2.5m, 3m, 4m, 5m, 6m, 7m, 8m, 10m