

Standard Duty Flat Web Sling SEN series

For USA



SEN1-1

Plies of Web			One Ply						Two Ply					
i-lift No.			2314301	2314302	2314303	2314304	2314305	2314306	2314307	2314308	2314309	2314310	2314311	2314312
Model			SEN1-1	SEN1-2	SEN1-3	SEN1-4	SEN1-5	SEN1-6	SEN2-1	SEN2-2	SEN2-3	SEN2-4	SEN2-5	SEN2-6
Web Width (in.)			1	2	3	4	5	6	1	2	3	4	5	6
Rated Capacity (lbs)	Vertical		2400	4800	6600	8800	11000	13200	4800	9600	12500	15500	19400	23000
	Choker		2560	3840	5280	7040	8800	10560	3840	7680	10000	12400	15520	18400
	Vertical Basket		4800	9600	13200	17600	22000	26400	9600	19200	25000	31000	38800	46000
	≥60° Basket		4080	8160	11220	14960	18700	22440	8160	16320	21250	26350	32980	39100
	45°≤Y60° Basket		3360	6720	9240	12320	15400	18480	6720	13440	17500	21700	27160	32200
	30°≤Y45° Basket		2400	4800	6600	8800	11000	13200	4800	9600	12500	15500	19400	23000

Usual length 3ft, 4ft, 5ft, 6ft, 8ft, 10ft, 12ft, 15ft, 20ft, 25ft, 30ft.

Standard Duty Flat Web Sling SFW series

For USA

- All i-LIFT flat webbing slings meet or exceed current U.S. industry and government requirements of OSHA and ASME B30.9, and can be modified according to local standard as required.
- Class 5 webbing possessing a minimum certified tensile strength of 6800lbs/in. width.



SFW2-2



SFW1-2

Plies of Web			One Ply						Two Ply					
i-lift No.			2314401	2314402	2314403	2314404	2314405	2314406	2314407	2314408	2314409	2314410	2314411	2314412
Model			SFW1-1	SFW1-2	SFW1-3	SFW1-4	SFW1-5	SFW1-6	SFW2-1	SFW2-2	SFW2-3	SFW2-4	SFW2-5	SFW2-6
Web Width (in.)			1	2	3	4	5	6	1	2	3	4	5	6
Eye Length (in.)			8.5	10	11	12	14	16	8.5	10	11	12	14	16
Rated Capacity (lbs)	Vertical		1200	2400	3600	4800	6000	7200	2400	4800	6500	8600	10200	12300
	Choker		1280	2480	2880	3840	4800	5760	2560	3840	5200	6880	8160	9840
	Vertical Basket		3200	6200	7200	9600	12000	14400	4800	9600	13000	17200	20400	24600
	≥60° Basket		2720	5270	6120	8160	10200	12240	4080	8160	11050	14620	17340	20910
	45°≤Y60° Basket		2240	4340	5040	6720	8400	10080	3360	6720	9100	12040	14280	17220
	30°≤Y45° Basket		1200	2400	3600	4800	6000	7200	2400	4800	6500	8600	10200	12300

Usual length 3ft, 4ft, 5ft, 6ft, 8ft, 10ft, 12ft, 15ft, 20ft, 25ft, 30ft.