

Floor Jack HF series

- Features a one-piece lift arm with dual leveling mechanism and reinforced flanged side frames for added strength under load.
- Patented safety bypass system prevents overextension and accidental overloading.
- Double swivel saddle and heavy steel casters allow safe, easy positioning.



i-lift No.	2315301	2315302	2315303	2315304	2315305	2315306
Model	HF20A	HF20D	HF23A	HF30A	HF23B	HF30B
Capacity (kg)	2000		2250	3000	2250	3000
Min./Max. Height (mm)	135/385	135/342	135/385	135/395	135/490	
Overall Size (mm)	550x212x140	471x199x135	550x212x140	628x252x168	693x346x176	660x346x180
Packing Size (mm)	555x235x155	480x210x145	555x235x155	640x267x179	735x386x181	738x385x203
Net Weight (kg)	12	9.5	13	19	34	36
Safety Std.	CE/GS		ANSI/ASME	CE/GS		
Application	Light duty				Heavy duty	

Long Chassis Service Jacks HF series

Professional class

- Welded base and cylinder to assure strength and eliminate leaks.
- Chromed pump piston and ram for added rust resistance.
- Foot pedal brings saddle up to load quickly.
- **Meets ANSI/ASME PALD standard & CE/GS standard.**



i-Lift No.	2315401	2315402	2315403	2315404	2315405	2315406
Model	HF20C	HF30C	HF50C	HF50H	HF100C	HF100H
Capacity (tonne)	2	3	5	5	10	10
Max. Saddle Height (mm)	800	600	560	685	560	685
Min. Saddle Height (mm)	140	130	150	150	160	160
Net Weight (kg)	58	70	95	95	145	145