

Low Profile Floor Scale NA series

- ▲ Rugged steel diamond plate surface with heavy duty welded channel support.
- ▲ Overload protection to 150% of capacity, adjustable leveling feet, can be pit mounted or free standing.
- ▲ Four alloy tool steel potted load cells.
- ▲ Durable power coat finish, 6 digit 7 segment display, bi-directional RS232 port, and operator controls for Zero, Tare, Unit, net/gross and print. Converts to lb. or kg. readout.
- ▲ Deluxe stainless steel indicator as standard.
- ▲ Two slopes are optional equipments.
- ▲ Slopes LE36, LE48, LE60.



NA2000A
Standard NA includes
a stainless steel indicator.



Optional Slope

i-Lift No.	1210601	1210602	1210603	1210604	1210605
Model	NA1000	NA2000A	NA2000B	NA5000A	NA5000B
Measuring Range (kg)	1000	2000		5000	
Indexing Accuracy (kg)	0.2	0.5		1	
Sensor Capacity (kg)	1000	2000		2500	
Sensor Number			4		
Platform Size (mm)	915x915	1220X1220	1500X1500	1220X1220	1500X1500
Height (mm)			70		
Net Weight (kg)	75	145	180	160	200
Equipment Temperature	-10℃~+40℃ relative temperature<95%				
Sensor Temperature	-20℃~+60℃				
Voltage	110V AC (-10%, +10%) 50 Hz				
Accuracy Class	3				
Slope	O	O	O	O	O

O = Option

Slopes LE series

i-Lift No.	1211101	1211102	1211103
Model	LE36	LE48	LE60
Width (mm)	915 (36inch)	1220 (48inch)	1500 (59inch)
Length (mm)		915 (36inch)	
Angle (°)		4.45	
Net Weight (kg)	48 (106lbs)	63 (139lbs)	77 (170lbs)



LE36