

Floor Lock FR series

- ▲ Universal for different applications.
- ▲ Prevents accidental rolling and stabilizes stationary loads on platform trucks, fixture dollies, and other castered equipment. Locks when large friction face is pressed against floor. Simple foot pressure easily engages and disengages lock.
- ▲ Rubber padding is vulcanized to lock, preventing separation and ensuring floor protection. Zinc plated to guard against corrosion.



FR07



FR04



FR08



FR06

i-Lift No.		1311701	1311702	1311703	1311704	1311705	1311706	1311707	1311708
Model		FR01	FR02	FR03	FR04	FR05	FR06	FR07	FR08
Top Plate Size	mm(in.)	4x114(4.5)						5x184(7.3)	
Mounting Height	mm(in.)	143(5.6)	165(6.5)	185(7.3)	190(7.5)	240(9.5)	250(10.1)	200(8)	267(10.5)
Used with Castor Size	mm(in.)	100(4)	125(5)	150(6)	150(6)	200(8)	200(8)	150(6)	200(8)
Net Weight	kg(lb.)	1.4(3.1)	1.42(3.1)	1.46(3.2)	1.47(3.2)	1.57(3.5)	1.6(3.5)	2.8(6.2)	2.9(6.4)

Adjustable Work Positioners XL series

- ▲ Reduces strain-positions your work at the precise height and angle you select.
- ▲ Choose table height range 510-700mm or 720-1070mm great for dies, mould, parts bin, etc.
- ▲ Lightweight, mobile, all-steel construction.
- ▲ Platform can be set at various heights and tilted to a certain angle to reduce strain and overexertion.
- ▲ Telescoping shaft with safety lever secures the work positioners to the height you want.
- ▲ Four swivel casters making the work positioners extremely easy to maneuver.
- ▲ Angle of table is adjustable from 0-40°.
- ▲ A valve core for pneumatic purpose.

i-Lift No.		1311501	1311502	1311503
Model		XL15A	XL15B	XL15C
Capacity	kg(lb.)	150(330)		
Table Size	(mm)(in.)	510x410(20x16.1)		
Table Height Range	(mm)(in.)	510-700(20-27)	720-1070(28-42)	720-970(28-38)
Adjustable Table Angle		0-40°	0-40°	0°
Net Weight	kg(lb.)	28(61.6)	30(66)	23(50.6)



XL15A

XL15B

Hydraulic Work Positioner XH series

- ▲ Reduces strain-positions your work at the precise height and angle you select.
- ▲ Table height 720-1070mm great for dies, mould, parts bin, etc.
- ▲ Lightweight, mobile, all-steel construction.
- ▲ Platform can be set at various heights and tilted to a certain angle to reduce strain and overexertion.
- ▲ Hydraulic pump lift the platform to the height you want.
- ▲ Four swivel casters making the work positioners extremely easy to maneuver.

i-Lift No.		1311601	1311602	1311603
Model		XH15	XH20	XH25
Capacity	kg(lb.)	150(330)	200(440)	250(550)
Table Size	(mm)(in.)	503x405(20x16)		
Table Height Range	(mm)(in.)	725-1080(28.5x42.5)		
Adjustable Table Angle		0-40°		
Net Weight	kg(lb.)	38(83.6)	38(83.6)	39(85.8)

