

Stationary Lift Table HW series

- ▲ Heavy Duty Design
- ▲ HW series lift tables meet EN norm and ANSI/ASME safety standards.
- ▲ These models can be used in above-floor or in-floor pit applications.

Standard Safety Features

- ▲ Upper platform lifted with aluminum safety bar preventing descent on contact with obstructions.
- ▲ Low-tension (24V) control box with up-down buttons.
- ▲ Internal power pack equipped with relief valve against overloading and compensated flow valve for controlled lowering speed.
- ▲ Heavy duty cylinders with drainage system and check valve to stop the lift table lowering in case of hose burst.
- ▲ Safety clearance between scissors to prevent trapping during operation.

Other Standard Features

- ▲ Self lubricating bushings on pivot points.
- ▲ Removable lifting eye to facilitate handling and lift table installation.
- ▲ High quality AC power packs are made in Europe.



Removable lifting eye



HW4001

i-lift No.		1312001	1312002	1312003	1312004	1312005	1312006	1312007	1312008
Model		HW 1001	HW 1002	HW 1003	HW 1004	HW 1005	HW 1006	HW 1007	HW 1008
Capacity	kg(lb.)	1000(2200)							
Lowered Height	(mm)(in.)	205(8.1)			240(9.4)				
Raised Height	(mm)(in.)	990(39)			1300(51.1)				
Platform Size	(mm)(in.)	820×1300 (32.3x51.2)	1000×1600 (40x63)	850×1700 (33.5x67)	1000×1700 (40x67)	850×2000 (33.5x80)	1000×2000 (40x80)	1700×1500 (67x60)	2000×1700 (80x67)
Base Frame Size	(mm)(in.)	680×1266(26.8x49.8)			680×1600(26.8x63)			1600×1362(63x53.6)	
Lift Time	(second)	20~25			30~35			30~40	
Power Pack		380V/50HZ, AC 1.1kw							
Net Weight	kg(lb.)	160(352)	186(409.2)	200(440)	210(462)	212(466.4)	223(490.6)	365(803)	430(946)

i-lift No.	1312009	1312010	1312011	1312012	1312013	1312014	1312015	1312016
Model	HW2001	HW2002	HW2003	HW2004	HW2005	HW2006	HW2007	HW2008
Capacity	kg(lb.) 2000(4400)							
Lowered Height	(mm)(in.) 230(9.1)		250(9.8)					
Raised Height	(mm)(in.) 1000(40)		1300(51.1)				1400(55.1)	
Platform Size	850×1300 (33.5x51.2)	1000×1600 (40x63)	850×1700 (33.5x67)	1000×1700 (40x67)	850×2000 (33.5x80)	1000×2000 (40x80)	1700×1500 (67x60)	2000×1800 (80x70.9)
Base Frame Size	(mm)(in.) 785×1255(31x49.4)			785×1630(31x64.2)			1630×1435(64x56.5)	
Lift Time	(second) 20~25		25~35					
Power Pack	380V/50HZ,AC 2.2kw							
Net Weight	kg(lb.) 235(517)	268(589.6)	289(635.8)	300(660)	300(660)	315(693)	415(913)	500(1100)

i-lift No.		1312017	1312018	1312019	1312020	1312021	1312022	1312023	1312024
Model		HW4001	HW4002	HW4003	HW4004	HW4005	HW4006	HW4007	HW4008
Capacity	kg(lb.)	4000(8800)							
Lowered Height	(mm)(in.)	240(9.4)		300(11.8)				350(17.8)	
Raised Height	(mm)(in.)	1050(41.3)		1400(55.1)				1300(51.1)	
Platform Size	(mm)(in.)	1200×1700 (47.2x67)	1200×2000 (47.2x80)	1000×2000 (40x80)	1200×2000 (47.2x80)	1000×2200 (40x86.6)	1200×2200 (47.2x86.6)	1700×1500 (67x60)	2200×1800 (48.6x70.9)
Base Frame Size	(mm)(in.)	930×1600(36.6x63)			930×1980(36.6x78)			1655×1432(65.2x56.5)	
Lift Time	(second)	30~40		45~50				35~45	
Power Pack		380V/50HZ,AC 2.2kw							
Net Weight	kg(lb.)	375(825)	405(891)	470(1034)	490(1078)	480(1056)	505(1111)	570(1254)	655(1441)