

## Stationary Lift Table HW series

- ▲ Large platform for special size materials.
- ▲ Meet EN1570 norm and ANSI/ASME safety standard.
- ▲ High quality power unit made in Europe.



i-Lift No.		1312501	1312502	1312503
Model		HW500L	HW501	HW502
Capacity	kg(lb.)		500(1100)	
Lowered Height	(mm)(in.)		200(8)	
Raised Height	(mm)(in.)		1000(40)	
Platform Size	LxW (mm)(in.)	800x2000(31.5x80) (standard)	1300x600(51x23.6)	1300x800(51x31.5)
Base Frame Size	(mm)(in.)	680x1615(26.5x63.6)	1210x585(47.6x23)	
Lift Time	(sec)	20~25	10~15	
Power Pack		380V/50HZ, AC 1.1kw	380V/50HZ, AC 0.75KW	
Net Weight	kg(lb.)	193(424.6)	121(266.2)	131(288.2)

## Larger Lift Table HW·D series

- ▲ Large platform for special size materials.
- ▲ Heavy Duty Design.
- ▲ Meet EN1570 norm and ANSI/ASME safety standards.
- ▲ These models can be used in above-floor or in-floor pit applications.

### Standard Safety Features

- ▲ Upper platform lifted with aluminum safety bar preventing descent on contact with obstructions.
- ▲ Low-tention (24V) control box with up-down buttons, and compensated flow valve for controlled lowering speed.
- ▲ Heavy duty cylinders with drainage system and check valve to stop the lift table lowering in case of hose burst.
- ▲ Safety clearance between scissors to prevent trapping during operation.

### Other Standard Features

- ▲ Self lubricating bushings on pivot points.
- ▲ Removable lifting eye to facilitate handling and lift table installation.
- ▲ High quality AC power packs are made in Europe.



HW2000D

i-Lift No.		1312601	1312602	1312603
Model		HW2000D	HW4000D	HW8000D
Capacity	kg(lb.)	2000(4400)	4000(8800)	8000(1760)
Lowered Height	(mm)(in.)	205(8.1)	230(9)	240(9.4)
Raised Height	(mm)(in.)	1000(40)	1000(40)	1050(41.3)
Platform Size	LxW (mm)(in.)	2500x820(100x32.3)	2500x850(100x33.5)	3000x1200(118x47.2)
Base Frame Size	(mm)(in.)	2460x680(97x26.8)	2450x785(96.5x30.9)	2970x930(116.9x36.6)
Lift Time	(sec)	40~45	30~40	40~50
Power Pack		380V/50Hz, AC1.1kw	380V/50Hz, AC2.2kw	380V/50Hz, AC2.2kw
Net Weight	kg(lb.)	265(583)	360(792)	705(1551)