

## “U” Low Lift Table HU series

- ▲ “U” Shaped Top Platform
- ▲ “U” shaped table are specially made for handling pallets, no need for a pit or load.
- ▲ They are manufactured to all European safety standards including EN1570:1999.
- ▲ Remote power pack with pedestal and controls, IP54 protection.
- ▲ Upper platform fitted with safety perimeter to prevent descent on contact with obstructions.
- ▲ 24V control box with UP and DOWN buttons and emergency stop.
- ▲ External power pack equipped with a relief valve against overloading and a compensated flow valve for controlling lowering speed.
- ▲ Hose burst safety valve to stop the lift table lowering in case of hose breakage.
- ▲ Removable lifting eyes to facilitate handling and installation of the lift table.
- ▲ Oil-less bushings on pivot points.
- ▲ Quick assembly joint for oil hose.



HU1000



HU1000  
(Min. Height)



HU1000  
(Max. Height)

NEW

i-Lift No.	1312701	1312702	1312703	1312704
Model	HU600	HU1000	HU1500	HU2000
Capacity kg(lb.)	500(1100)	1000(2200)	1500(3300)	2000(4400)
Max. Height (mm)(in.)	860(34)			
Collapsed Height (mm)(in.)	85(3.3)		105(4.1)	
Platform LxW (mm)(in.)	1450x985(57.1x38.8)	1450x1140(57.1x44.9)	1600x1180(63x46.5)	1500x1150(60x45.3)
Lift Time (sec)	25~35		30~40	20
Power Pack	380V/50Hz, AC 0.75KW	380V/50Hz, AC 0.75KW	380V/50Hz, AC 1.5KW	380V/50Hz, AC 2.2KW
Net Weight kg(lb.)	207(455.4)	280(616)	380(836)	306(673.2)

Note: Clearance between two forks for pallet truck access 585mm.