

## Low Profile Lift Table HY Series

- ▲ Heavy duty design with larger platform
- ▲ These tables achieve a low closed height, eliminating the need for a pit installation.
- ▲ They are manufactured to all European safety standards including EN1570:1999.
- ▲ Remote power pack with pedestal and controls, IP54 protection.
- ▲ Upper platform fitted with safety perimeter to prevent descent on contact with obstructions.
- ▲ 24V control box with UP and DOWN buttons and emergency stop.
- ▲ External power pack equipped with a relief valve against overloading and a compensated flow valve for controlling lowering speed. Power supply are AC 380V/50HZ/3phase.
- ▲ Hose burst safety valve to stop the lift table lowering in case of hose breakage.
- ▲ Removable lifting eyes to facilitate handling and installation of the lift table.
- ▲ Oil-less bushings on pivot points.
- ▲ Loading ramp is a standard equipment.



i-Lift No.	1312801	1312802	1312803	1312804	1312805	1312806	1312807	1312808	1312809	1312810
Model	HY1001	HY1002	HY1003	HY1004	HY1005	HY1501	HY1502	HY1503	HY2001	HY2002
Capacity (kg)(lb.)	1000(2200)					1500(3300)			2000(4400)	
Platform Size LXW(mm)(in.)	1450×1140 (57.1x44.9)	1600×1140 (63x44.9)	1450×800 (57.131.5)	1600×800 (63x31.5)	1600×1000 (63x40)	1600×800 (63x31.5)	1600×1000 (63x40)	1600×1200 (63x47.2)	1600×1200 (63x47.2)	1600×1000 (63x40)
Min. Height (mm)(in.)	85(3.3)					105(4.1)				
Max. Height (mm)(in.)	860(33.9)					870(34.3)				
Stroke (mm)(in.)	775(30.5)									
Lifting Time (second)	25					30			35	
Power Pack	380V/50HZ,AC 0.75kw					380V/50HZ,AC 2.2kw			380V/50HZ,AC 2.2kw	
Net Weight (kg)(lb.)	357(785.4)	364(800.8)	326(717.2)	332(730.4)	352(774.4)	367(807.4)	401(882.2)	415(913)	419(921.8)	405(891)