

Hand Pallet Truck AC series

- ▲ Rubber coated handle comfortable even under extreme temperature conditions.
- ▲ Fully sealed hydraulic unit housing.
- ▲ Single valve cartridge for easy maintenance.
- ▲ Powder coated chassis made of high grade steel.
- ▲ **Conforms to EN1757-2.**

NEW



AC25S



i-Lift No.		1112301	1112302	1112303	1112304
Model		AC25S	AC25L	AC30S	AC30L
Capacity	kg(lb.)	2500(5500)		3000(6600)	
Max. Fork Height	mm(in.)	200 or 190(8 or 7.5)			
Min. Fork Height	mm(in.)	85 or 75(3.3 or 3)			
Fork Length	mm(in.)	1150(45.3)	1220(48)	1150(45.3)	1220(48)
Fork Overall Width	mm(in.)	540(21.3)	685(27)	540(21.3)	685(27)
Fork Width	mm(in.)	160(6.3)			
Front Wheel	mm(in.)	Φ80×70 or Φ74×70 (Φ3×2.8 or Φ3×2.8), Nylon,Polyurethane			
Steer Wheel	mm(in.)	Φ200 or Φ180x50 (Φ8 or Φ7×2), Nylon,Polyurethane,Rubber			
Net Weight	kg(lb.)	75(165)	78(171.6)	78(171.6)	81(178.2)

Hand Pallet Truck DFA series

- ▲ Bushings at key points.
- ▲ Super strong steel structure frame.
- ▲ Tapered fork tips with entry guide roller.
- ▲ Fully adjustable push rods on forks.
- ▲ **Conforms to EN1757-2.**

NEW



DFA25S



i-Lift No.		1112401	1112402	1112403	1112404
Model		DFA25S	DFA25L	DFA30S	DFA30L
Capacity	kg(lb.)	2500(5500)		3000(6600)	
Max. Fork Height	mm(in.)	200 or 190(8 or 7.5)			
Min. Fork Height	mm(in.)	85 or 75(3.3 or 3)			
Fork Length	mm(in.)	1150(45.3)	1220(48)	1150(45.3)	1220(48)
Fork Overall Width	mm(in.)	550(21.7)	685(27)	550(21.7)	685(27)
Fork Width	mm(in.)	160(6.3)			
Front Wheel	mm(in.)	Φ80×70 or Φ74×70 (Φ3×2.8 or Φ3×2.8),Nylon,Polyurethane			
Steer Wheel	mm(in.)	Φ200 or Φ180x50 (Φ8 or Φ7×2),Nylon,Polyurethane,Rubber			
Net Weight	kg(lb.)	72(158.4)	75(165)	75(165)	78(171.6)