

Lift Table BSL series

- ▲ Heavy duty range
- ▲ New design to meet norm EN1570: 1999.
- ▲ New hydraulic system increases safety and protects your goods, tepless rate of lowering system remains irrespective of the weight of the load.

i-lift No.		1310410	1310411
Model		BS50LD	BS100LD
Capacity	kg(lb.)	500(1100)	1000(2200)
Min. Fork Height	mm(in.)	470(18.5)	520(20.5)
Max. Fork Height	mm(in.)	2000(80)	
Table Size	mm(in.)	1200x800(47.2x31.5)	
Handle Height	mm(in.)	1030(40.5)	1080(42.5)
Ground Clearance	mm(in.)	68.5(2.7)	125(5)
Wheel Dia	mm(in.)	Φ160(6.3)	Φ200(8)
Lowering time	sec	22	44
Overall Size	mm(in.)	1430x800(56.3x31.5)	
Net Weight	kg(lb.)	222(488.4)	242(532.4)



Electric Lift Table ESL series

- ▲ Good quality.
- ▲ Save labor and improve work efficiency.
- ▲ Built-in charger, charge display meter.
- ▲ Output 12V, DC 8A.
- ▲ Made in China, rising steadily and forcefully.
- ▲ High quality maintenance free battery, saving maintenance time and cost, power lasting.
- ▲ 2 swivel casters and 2 fixed casters, casters with protective devices.
- ▲ Design of Scissor with anti clip, with overload protection function, more reliable, more secure.

i-lift No.		1310508	1310509
Model		ES50LD	ES100LD
Capacity	kg(lb.)	500(1100)	1000(2200)
Min. Fork Height	mm(in.)	520(20.5)	520(20.5)
Max. Fork Height	mm(in.)	2000(80)	
Table Size	mm(in.)	1200x800(27.2x31.5)	
Handle Height	mm(in.)	1089(42.9)	1089(42.9)
Ground Clearance	mm(in.)	30(1.2)	30(1.2)
Wheel Dia.	mm(in.)	Φ200(8)	Φ200(8)
Lifting/Lowering Tiem	sec	20/25	30/35
Lifting Times with full power		100	60
Power	kw	0.8	1.6
Battery	Ah/V	80/12	90/12
Battery Charger		12V/8A	
Overall Size	mm(in.)	1430x800(56.3x31.5)	
Net Weight	kg(lb.)	266(585.2)	286(629.2)

