

Electric Pallet Truck RB15

- ▲ Permanent magnet drive motor, compact structure, easy maintenance.
- ▲ Stepless speed control system, easy to operate.
- ▲ Battery open design, easy to replacement.
- ▲ Built-in charger is standard.
- ▲ Sealed batteries free of maintenance, safe operation and no pollution.
- ▲ Small body, suitable for narrow space.
- ▲ Fork fit for double-deck pallet.
- ▲ Automatic lifting limit, safety, energy saving.
- ▲ Emergency reversing device and emergency brake switch.
- ▲ Low noise, low energy consumption, every day only 2 kW-h.



RB15

i-lift No.		1112701
Model		RB15
Drive unit		Electric
Operator type		Walkie
Capacity	kg(lb.)	1500(3300)
Load center	mm(in.)	600(23.6)
Wheelbase	mm(in.)	1301(51.2)
Wheel material (Driving/balance/front wheel)		PU
Wheel number (Driving/balance/front wheel)	piece	1/0/2
Driving wheel size	mm(in.)	Φ210×70(8.3×2.8)
Front wheel size	mm(in.)	Φ74×93(2.9×3.7)
Min. fork height	mm(in.)	75(3)
Max. fork height	mm(in.)	185(7.3)
Max.lifting height	mm(in.)	110(4.3)
Outside width between forks	mm(in.)	680(26.7)
Inside width between forks	mm(in.)	360(14.2)
Fork length	mm(in.)	1220(48)
Fork width	mm(in.)	160(6.3)
Fork thickness	mm(in.)	50(2)
Overall length	mm(in.)	1707(67.2)
Overall width	mm(in.)	680(26.7)
Overall height	mm(in.)	1210(47.6)
Aisle width for pallets 1000×1200 crossways	mm(in.)	1884(74.2)
Aisle width for pallets 800×1200 lengthways	mm(in.)	1934(76.1)
Turning radius	mm(in.)	1473(58)
Travel speed,with load /without load	km/h	3/3.5
Max.gradeability,with load/without load	%	6/10
Service brake		Electromagnetic brake
Drive motor	kw	DC 0.75
Lift motor	kw	DC 0.8
Battery voltage/capacity		2X12V/70Ah
Battery weight	kg(lb.)	18.8X2(82.9)
Truck weight	kg(lb.)	185(407)

