

Electric Pallet Truck EPT series

- ▲ Overall simplification and long service life
- ▲ The integrated control module of the handle makes operation more convenient;
- ▲ Lithium battery drive, safe and reliable;
- ▲ The driver module realizes electrical integration, has a simple structure, and is not easily damaged.



EPT15V



i-lift No.		1213201	1213202
Model		EPT15V	EPT20V
Type		Electric	
Capacity	kg(lb.)	1500(3300)	2000(4400)
Load Center Distance	mm(in.)	600(23.6)	
Load Distance, Centre of Drive Axle to Fork	mm(in.)	950(37.4)	
Wheel Base	mm(in.)	1270(47.2)	
Driving Wheel Size	mm(in.)	Φ210×75(8.3x3)	
Roller Size	mm(in.)	Φ80×70(3.1x2.8)	
Max. Fork Height	mm(in.)	195(7.7)	
Height of tiller in Drive position Min./Max.	mm(in.)	585/1250(23/49)	
Min.Fork Height	mm(in.)	85(3.3)	
Overall Length	mm(in.)	1620(63.8)	
Length to Face of Fork	mm(in.)	470(18.5)	
Overall Width	mm(in.)	550/685(21.7/27)	
Dimension of Fork	mm(in.)	50x160x1150(2x6.3x45.3)	
Distance between fork-arms	mm(in.)	550/685(21.7/27)	
Ground Clearance	mm(in.)	35(1.4)	
Aisle Width for Pallets 1000x1200 Crossways	mm(in.)	1820(71.7)	
Aisle Width for Pallets 800x1200 Crossways	mm(in.)	1870(73.6)	
Turning Radius	mm(in.)	1380(54.3)	
Travel Speed,laden/unladen	Km/h	4.2/4.5	
Max.Gradeability,laden/unladen	%	6/10	
Drive Motor Power	Kw	0.75	0.9
Lift Motor Power	Kw	0.5	
Battery Voltage,Nomical Capacity	V/Ah	24/20(30)	48/15(20)
Battery Weight	kg(lb.)	5.5(12.1)	
Net Weight (Without Battery)	kg(lb.)	142(312.4)	145(319)