

Self-Propelled Scissor Work Platform GKPT series

- ▲ Emergency stop at both platform and ground controls.
- ▲ Charging indicator.
- ▲ Pothole guards.
- ▲ Maintenance bar.
- ▲ Manual platform lowering valve.
- ▲ Safety entrance door.
- ▲ Descent alarm.
- ▲ Solid non-marking tires.
- ▲ Tilt level sensor with audible alarm.



GKPT0407

i-lift No.		2422201	2422202
Model		GKPT0307	GKPT0407
Capacity/Extension Capacity	kg(lbs)	240(528)/100(220)	
Max. Occupants		2	
Max. Working Height	mm(inch)	5500(216.5)	5900(232.3)
Max. Platform Height	mm(inch)	3000(118)	3900(153.5)
Min. Platform Height	mm(inch)	760(30)	850(33.5)
Overall Length(with ladder/without ladder)	mm(inch)	1350(53)/1200(47.2)	
Overall Width	mm(inch)	760(30)	
Overall Height(Rails up/Rails down)	mm(inch)	1860(73.2)/1530(60)	1950(76.8)/1620(63.8)
Platform Size	mm(inch)	1200x700(47.2x27.5)	
Platform Extension Size	mm(inch)	600(23.6)	
Max. Travel Speed(Stowed)	km/h	4	
Max. Travel Speed(Raised)	km/h	0.5	
Min. Turning Radius	mm(inch)	0	
Gradeability	%	25	
Max. Working Slope	°	2°/3°	
Tyres(Drive Motors)	mm(inch)	Φ230x80(9x3)	
Tyres(Front Wheels)	mm(inch)	Φ150x50(6x2)	
Lifting Motor	V/kw	2x24/0.4	
Driving Motor	V/kw	24/0.8	
Up/Down Speed	s	30/20	35/20
Ground Clearance(Stowed/Raised)	mm(inch)	60/15(2.4/0.6)	
Battery	V/Ah	2x12/80	
Integrated Charger	V/A	24/8	
Net Weight	kg(lbs)	720(1584)	760(1672)

