

Powered Drive Straddle Trucks HH1216JW

- ▲ High-strength frame designed for tough pallet handling tasks.
- ▲ Lower consumption, Lower service cost, while higher performance.
- ▲ 24V/85AH maintenance free battery contributes to strong power and easier operation.
- ▲ Compact structure and reasonable layouts provides steadiness and durability during operation.
- ▲ This unit features Forks Inside Adjustable Straddle Legs that are adjustable from 9-½" I.D. to 31" O.D., ideal for Pallets or Skids.



HH1216JW



i-Lift No.		1551421
Model		HH1216JW
Drive unit		Electric
Operator type		Pedestrian
Load Capacity	kg(lb.)	1200(2650)
Load Center	mm(in.)	600(23.6)
Overall Length	mm(in.)	1575(62)
Overall Width	mm(in.)	1206~1510(47.5~59.5)
Overall Height	mm(in.)	2160(85)
Fork Length	mm(in.)	1066(42)
Fork Width	mm(in.)	540(21.3)
Lowered Height	mm(in.)	65(2.5)
Overall Fork Width	mm(in.)	240~780(9.5~31)
Max. Fork Height	mm(in.)	1575(65)
Straddle Leg Width	mm(in.)	965~1270(38~50) I.D, 1200~1510(47.5~59.5) O.D
Travelling speed (Loaded/Unloaded)	mm(in.)	2.5/3
Travel Motor	(kw/V)	0.75
Lift Motor	(kw/V)	2.2
Net Weight	kg(lb.)	636(1400)

