

Electric Pallet Truck

H·HM series

- ▲ Handle integrated battery display and operation control, more convenient.
- ▲ Drive unit with electromagnetic brake.
- ▲ Comply with CE European safety standards.

HD-HM series

- ▲ Small but strong frame design, good for operating in narrow aisle.
- ▲ The battery is light and easy to replace. It can be replaced quickly in 20 seconds, can never be cut off.
- ▲ 48V15Ah lithium iron phosphate battery.

HQ-HM series

- ▲ Small but strong frame design, good for operating in narrow aisle.
- ▲ Large capacity battery, 48V30Ah lead acid battery.

HK-HM series

- ▲ Strong steel structure design makes it more durable.
- ▲ Large capacity battery, 48V30Ah lead acid battery.



HD18-HM



HQ20-HM



HK30-HM

i-Lift No.		1111401	1111402	1111403	1111404	1111405	1111406
Model		HD18-HM	HD20-HM	HQ20-HM	HQ25-HM	HQ30-HM	HK30-HM
Drive unit		Electric					
Load Capacity	kg(lb.)	1800(3960)	2000(4400)	2000(4400)	2500(5500)	3000(6600)	3000(6600)
Load Center	mm(in.)	600(23.6)	475(18.7) 510(20)	475(18.7)		510(20)	475(18.7) 510(20)
Overall Length	mm(in.)	1610(63.4)	1550(61) 1620(63.8)	1620(63.8)		1690(66.5)	1590(62.6) 1660(65.4)
Overall Width	mm(in.)	680(26.8)	550(21.7) 680(26.8)	550(21.7)		680(26.8)	550(21.7) 680(26.8)
Overall Height	mm(in.)	1265(49.8)	1280(50.4)		1280(50.4)		1280(50.4)
Fork Length	mm(in.)	1220(48)	1150(45.3) 1220(48)	1150(45.3)		1220(48)	1150(45.3) 1220(48)
Individual Fork Width	mm(in.)	160(6.3)	160(6.3)		160(6.3)		160(6.3)
Overall Fork Width	mm(in.)	680(26.8)	550(21.7) 680(26.8)	550(21.7)		680(26.8)	550(21.7) 680(26.8)
Max. Fork Height	mm(in.)	190(7.5)	195(7.7)		195(7.7)		195(7.7)
Min. Fork Height	mm(in.)	75(3)	80(3.1)		80(3.1)		80(3.1)
Front Load Roller	mm(in.)	Φ75x70(3x2.8)	Φ80x70(3.1x2.8)		Φ80x70(3.1x2.8)		Φ80x70(3.1x2.8)
Driving Wheel	mm(in.)	Φ190x70(7.5x2.8)	Φ210x70(8.3x2.8)		Φ210x70(8.3x2.8)		Φ210x70(8.3x2.8)
Max. Travel Speed	km/h	4.5	4.3		4.5		4.5
Service Brake		Electromagnetic brake					
Motive Power	kw		0.75	0.75	1	1.2	1.2
Battery Capacity	V/Ah		48/15		48/30		48/30
Charger		INPUT: AC 100-240V~50/60Hz 1.5A 150VA OUTPUT: DC 54.6V 2A					
Net Weight	kg(lb.)	140(308)	155(341)	185(407)	195(429)	200(440)	215(473)