

Manual Stacker HS series

- ▲ HS Series is not only an excellent compromise between price and performance but also a very resistant machine.
- ▲ Reinforced forks, steel pulley and forks precisely driven by rollers, are some of the main features of this stacker.
- ▲ The machine is also equipped with a foot pedal to lift forks, which considerably reduces the operator's effort.
- ▲ Option: Adjustable fork (320-870mm)



HS1525



adjustable fork



HS1016



i-lift No.		1551801	1551802	1551803	1551804	1551805	1551806	1551807	1551808
Model		HS0510	HS0516	HS1016	HS1018	HS1025	HS1030	HS1516	HS1525
Capacity	kg(lb.)	500(1100)		1000(2200)			1500(3300)		
Load Centre	mm(in.)	600(23.6)		600(23.6)			600(23.6)		
Max. Fork Height	mm(in.)	1000(40)	1600(63)	1600(63)	1800(70.9)	2500(98.4)	3000(118.1)	1600(63)	2500(98.4)
Min. Fork Height	mm(in.)	90(3.5)		90(3.5)			90(3.5)		
Fork Length	mm(in.)	1150(45.3)		1150(45.3)			1150(45.3)		
Fork Width	mm(in.)	100x48(4x1.9)		160x55(6.3x2.2)			160x55(6.3x2.2)		
Mast Width	mm(in.)	430(17)		480(19)		600(23.6)		490(19.3)	600(23.6)
Overall Fork width	mm(in.)	560(22)		560(22)			560(22)		
Min. Turning Radius	mm(in.)	1540(60.6)		1590(62.6)			1590(62.6)		
Steering Wheel	mm(in.)	150x50(3x2)		150x50(3x2)			150x50(3x2)		
Front Load Roller	mm(in.)	80x36(3.1x1.4)		80x60(3.1x2.4)			80x60(3.1x2.4)		
Overall size LxWxH	mm(in.)	1655x640x1380 (65.2x25.2x54.3)	1655x640x1970 (65.2x25.2x77.6)	1660x700x2005 (65.4x27.6x79)	1660x790x2210 (65.4x31.1x87)	1680x780x1760 (66.1x30.7x69.3)	1670x780x2020 (65.7x30.7x79.5)	1670x700x2085 (65.7x27.6x82)	1690x870x1760 (66.5x34.3x69.3)
Net Weight	kg(lb.)	126(277.2)	140(308)	173(380.6)	182(400.4)	259(569.8)	278(611.6)	182(400.4)	288(633.6)