

Stationary Lift Table HW series

- ▲ Heavy Duty Design
- ▲ HW series lift tables meet EN norm and ANSI/ASME safety standards.
- ▲ These models can be used in above-floor or in-floor pit applications.

Standard Safety Features

- ▲ Upper platform lifted with aluminum safety bar preventing descent on contact with obstructions.
- ▲ Low-tention (24V) control box with up-down buttons.
- ▲ Internal power pack equipped with relief valve against overloading and compensated flow valve for controlled lowering speed.
- ▲ Heavy duty cylinders with drainage system and check valve to stop the lift table lowering in case of hose burst.
- ▲ Safety clearance between scissors to prevent trapping during operation.

Other Standard Features

- ▲ Self lubricating bushings on pivot points.
- ▲ Removable lifting eye to facilitate handling and lift table installation.
- ▲ High quality AC power packs are made in Europe.



Option with scales



HW6001

i-Lift No.		1312025	1312026	1312027	1312028	1312029	1312030	1312031	1312032	1312033
Model		HW6001	HW6002	HW6003	HW6004	HW6005	HW6006	HW6007	HW6008	HW6009
Rated capacity	(kg)	6000	6000	6000	6000	6000	6000	6000	6000	6000
Platform size	(mm)	1600x1000	1800x1000	1600x1400	1800x1400	1600x1500	1800x1500	1600x2000	1800x2000	2000x1000
Base frame size	(mm)	1560x1000	1560x1000	1560x1000	1560x1000	1560x1500	1560x1500	1560x1500	1560x1500	1955x1000
Min. height	(mm)	390	390	390	390	390	390	390	390	400
Max. height	(mm)	1150	1150	1150	1150	1150	1150	1150	1150	1600
Lift time	(s)	25-35	25-35	25-35	25-35	25-35	25-35	25-35	25-35	30-40
Power Pack		380V/50Hz, AC 2.2 kw								
Net weight	(kg)	540	555	586	605	670	690	728	752	675

i-Lift No.		1312034	1312035	1312036	1312037	1312038	1312039	1312040	1312041	1312042
Model		HW6010	HW6011	HW6012	HW6013	HW6014	HW6015	HW6016	HW8001	HW1201
Rated capacity	(kg)	6000	6000	6000	6000	6000	6000	6000	8000	12000
Platform size	(mm)	2200x1000	2000x1400	2200x1400	2000x1500	2200x1500	2000x2000	2200x2000	4000x2250	3000x1600
Base frame size	(mm)	1955x1000	1955x1000	1955x1000	1955x1500	1955x1500	1955x1500	1955x1500	1955x1000	2990x1500
Min. height	(mm)	400	400	400	400	400	400	400	550	770
Max. height	(mm)	1600	1600	1600	1600	1600	1600	1600	1750	2580
Lift time	(s)	30-40	30-40	30-40	30-40	30-40	30-40	30-40	40-80	65-75
Power Pack		380V/50Hz, AC 2.2 kw								380V/50Hz, AC 5.5kw
Net weight	(kg)	690	728	748	835	858	908	934	1880	2420

Lift Table Accessories



Wheel Chassis
Model no. OP01



Truck Handling Chassis
Model no. OP02



Non-slip Platform
Model no. OP03



Limit Switch
Model no. OP04



Manual Loading Flap
Model no. OP05



Mechanical Stop
Model no. OP06



Dual Function Foot Control Unit
Model no. OP07



Guard Rails With Gate
Model no. OP08



Turntable Rectangular
Model no. OP09



Turntable Circular
Model no. OP10



Roller Conveyors
Model no. OP11



External Power Pack Plastic Cover
Model no. OP12



Tipping Protection
Model no. OP13



Protective Skirts
Model no. OP14



Lifting Eye Bolts
Model no. OP15



Platform Ramp
Model no. OP16



Inspection Hatch
Model no. OP17



Reinforced Platform
Model no. OP18



Mechanical Locks
Model no. OP19



Roll-off Guard
Model no. OP20