

Lawn Lifting Table

IHM series

- ▲ Heavy duty range.
- ▲ Handle with tool box.
- ▲ Pneumatic tire with brake system for safe and easy handling over rough terrain.
- ▲ New design to meet norm EN1570: 1999.
- ▲ New hydraulic system increases safety and protects your goods, stepless rate of lowering system remains irrespective of the weight of the load.



IHM200

IHM300D

Optional Rotary Table Sold Separately

Security Lock

Brakes

i-Lift No.		6001007	6001008	6001009	6001010	6001011	6001012
Model		IHM200	IHM300	IHM300D	IHM500	IHM501	IHM750
Capacity	kg(lb.)	200(440)	300(660)	300(660)	500(1100)	500(1100)	750(1650)
Table Height H(Min./Max.)	mm(in.)	380/870 (15/34.3)	410/1000 (16.1/40)	545/1700 (21.5/66.9)	545/1110 (21.5/44)	345/1180 (13.6/46.5)	545/1110 (21.5/44)
With Attached Table H(Min./Max.)	mm(in.)	458/948 (18/37.3)	448/1078 (17.6/42.4)	630/1785 (24.8/70.3)	630/1195 (24.8/47)	423/1258 (16.7/49.5)	630/1195 (24.8/47)
Table Size	mm(in.)	700x520 (27.6x20.5)	850x520 (33.5x20.5)	1010x520 (40x20.5)		1220x610 (48x24)	1010x520 (40x20.5)
Overall Size	mm(in.)	922x690x910 (36.3x27.2x35.8)	1065x690x975 (41.9x27.2x38.4)	1270x720x975 (50x28.3x38.4)		1538x800x975 (60.6x31.5x38.4)	1270x720x975 (50x28.3x38.4)
Front Tire	mm(in.)	Φ200(8)		Φ300(12)		Φ300(12)	Φ330(13)
Rear Swivel Tire with Brake	mm(in.)	Φ200(8)		Φ250(10)		Φ200(8)	Φ250(10)
Foot Pedal to Max. Height	(times)	16	20	40	30	35	40
Net Weight Without Optional Rotary Table	kg(lb.)	60(132)	85(187)	145(319)	126(277.2)	175(385)	130(286)
Optional Rotary Table Size	mm(in.)	Φ 600(24)		710x500(28x20)		Φ 600(24)	710x500(28x20)
Net Weight of Attached Table	kg(lb.)	24(52.8)		40(88)		24(52.8)	40(88)