

Linear Actuator Scissor Lift Table LA series

- ▲ Mechanical-Electric lift table.
- ▲ No oil leaks. No hydraulic lift.
- ▲ Maximum starting frequency 10 times per minute.
- ▲ Built-in charger. Compact, space-saving.
- ▲ With 4 swivel mute casters.
- ▲ High strength plastic wheel carrier.
- ▲ Quiet operation.
- ▲ **Non-marking silence wheels & Casters (steel bracket) available.**



LA250-01



Steel wheel

i-lift No.		1313901	1313902	1313903	1313904	1313905	1313906
Model		LA100D-01	LA100D-02	LA150D-01	LA150D-02	LA250-01	LA250-02
Capacity	kg(lb.)	100(220)		150(330)		250(550)	
Table size	mm(in.)	800x500(31.5x20)	910x610(35.8x24)	800x500(31.5x20)	910x610(35.8x24)	800x500(31.5x20)	910x610(35.8x24)
Min./Max. table height	mm(in.)	410/1280(16/50.4)		410/1280(16/50.4)		355/830(14/32.7)	
Battery		24DC(2x12)-12Ah		24DC(2x12)-12Ah		24DC(2x12)-12Ah	
Lifting time without load	s	28-32		36-40		30-34	
Lowering time without load	s	24-28		34-38		30-34	
Lifting time with rated load	s	36-40		57-61		45-49	
Lowering time with rated load	s	24-28		34-38		30-34	
Max. working current		6A		8A		5.5A	
Charger		24V-DC-2A		24V-DC-2A		24V-DC-2A	
Working cycle / charged		130		70		140	
Max. linear actuator force	N	8000		10000		8000	
Castor wheel		4 Pcs Mute Castor wheels TPR Bracket 5" TDR wheels					
Overall Dimension (LxWxH)	mm(in.)	890x500x992 (35x20x39.1)	1000x610x992 (40x24x39.1)	890x500x992 (35x20x39.1)	1000x610x992 (40x24x39.1)	890x500x992 (35x20x39.1)	1000x610x992 (40x24x39.1)
Net weight	kg(lb.)	79(173.8)	82(180.4)	80(176)	83(182.6)	64(140.8)	67(147.4)