

Semi-Electric Stacker MSS-N series

- ▲ Heavy duty design and top quality mast construction.
- ▲ Safety guard on load roller and steering wheel.
- ▲ More power for big cap.
- ▲ More reliable mast steel imported from Germany.
- ▲ The attractive outline from professional stacker.
- ▲ Built-in charger for option.

i-Lift No.		1561101	1561102	1561103	1561104
Model		MSS1016N	MSS1023N	MSS1029N	MSS1035N
Capacity	kg(lb.)	1000(2200)			
Lift Height	mm(in.)	1600(63)	2350(92.5)	2900(114.2)	3500(137.8)
Fork Length	mm(in.)	1150(45.3)			
Fork Width	mm(in.)	550(21.7)			
Fork Dimension	mm(in.)	162X60(64x2.7)			
Overall Dimension (LxWxH)	mm(in.)	1690x750x1643 (66.5x29.5x64.7)	1690x750x1920 (66.5x29.5x66.5)	1690x750x2053 (66.5x29.5x92.5)	1690x750x2153 (66.5x29.5x84.8)
Lift Speed with/without load	mm/sec	85/100			
Min Fork Height	mm(in.)	85(3.3)			
Battery		DC12V120AH			
Motor of Hydraulic Pump		DC12V,2KW			



MSS1023N

Semi-Electric Stacker PY series

- ▲ Ergonomic design with handle for easy pulling and pushing the stacker.
- ▲ Strong brake castor for safety.
- ▲ Special frame design for heavy load 1000kg and 1500kg.
- ▲ Maintenance free battery.

(3.5-100)

i-Lift No.		1550201	1550202	1550203	1550204
Model		PY1025	PY1030	PY1525	PY1530
Capacity	(kg)(lb.)	1000(2200)		1500(3300)	
Load Center	(mm)(in.)	600(23.6)			
Lifting Height	(mm)(in.)	90-2500 (3.5-100)	90-3000 (3.5-118)	90-2500 (3.5-100)	90-3000 (3.5-118)
Fork Length	(mm)(in.)	1150(45.3)			
Fork Width	(mm)(in.)	560(22)			
Min. outside turning radius	(mm)(in.)	2000(80)		2100(82.7)	
Max.Lifting Speed With Full Loading	(m/min)	≥ 3.6			
Lower Speed		Controllable			
Lifting Motor	(W/V)	1600/12			
Battery	(Ah/V)	120/12			
Charger		220V/12V			
Overall Length	(mm)(in.)	1770(69.7)			
Overall Width	(mm)(in.)	700(27.6)		800(31.5)	
Overall Height	(mm)(in.)	1770(69.7)	2020(79.5)	1770(69.7)	2020(79.5)
Load Wheel Diameter	(mm)(in.)	80(3)			
Steering Wheel Diameter	(mm)(in.)	200(8)			
Net Weight	(kg)(lb.)	375(825)	405(891)	400(880)	430(946)



PY1025