

# High Lift Scissor Truck NH / NHE series

## Option

▲ **Economic version but reliable.**

▲ **Single stage cylinder.**

No decrease of capacity.

No risk of leakage.

No dangerous dropping of second stage cylinder.

▲ **High quality power unit made in USA.**

▲ **Safety:** Patented safety system on handle to prevent accidental touch of the release handle thus causing sudden sliding down of the fork, you can screw the release handle tight in slow or quick lifting position.

Quick lift as standard.

▲ **Conforms to EN1757-4.**



Ergonomic handle



NH10S



NH10S



NHE10S



NHE10S

i-Lift No.		1410801	1410802	1410803	1410804
Model		NH10S	NH10L	NHE10S	NHE10L
Capacity	kg(lbs)	1000(2200)			
Max. Fork Height	mm(inch)	800(31.5)			
Min. Fork Height	mm(inch)	85 ± 2(3.3 ± 0.1)			
Fork Overall Width	mm(inch)	540(21.3)	680(26.8)	540(21.3)	680(26.8)
Fork Length	mm(inch)	1150(45.3)			
Front Load Roller	mm(inch)	Ø75x75(3x3)			
Steering Wheel	mm(inch)	Ø180x50(7x2)			
Pump Strokes to Max. Height without load /with rated load		11/19	11/19	—	—
Lifting Time, without/with rated load	(sec)	—	—	11/19	11/19
Battery	(Ah/V)	—	—	66/12	66/12
Battery Charger	(A/V)	—	—	10/12	10/12
Net Weight (without battery)	kg(lbs)	110(242)	115(253)	141(310.2)	146(321.2)

\*\*\*1.5T capacity is available.