

Platform Stacker PFG series

▲ Simple and Easy Operation.

Lifting movement via collapsible foot pedal.
Sensitive lowering through sinking valve.
Overload protection via pressure valve.

▲ Safe Operation and secure Working Conditions.

Stable chassis with 2 frame rollers and 2 steering rollers.

▲ Long Service Life.

Robust construction.
Hard chromium plated frame.
Hardened chromium plated ram.
Stainless handrail for option.

▲ Effortless Movement.

Ball bearing rollers.
Polyurethane rollers.

▲ Non-marking castor as standard.

▲ Conforms to EN 1757-1:2001.



PFG4085

i-lift No.		1510301	1510302	1510303
Model		PFG4085	PFG4120	PFG4150
Capacity	kg(lb.)		400(880)	
Max. height to roll top	mm(in.)	970(38.2)	1320(52)	1620(63.8)
Min. height to roll top	mm(in.)		220(8.7)	
Min. height to leg with swivel wheels	mm(in.)		130(5.1)	
Work dia.	mm(in.)		200-600(8-24)	
Roll size	mm(in.)		76x550(3x21.7)	
Roll length	mm(in.)		550(21.7)	
Roll work center	mm(in.)		180(7.1)	
Roll material			PU	
Overall size	mm(in.)	780x630x1070 (30.7x24.8x42.1)	780x630x1420 (30.7x24.8x55.9)	780x630x1720 (30.7x24.8x67.7)
Front wheels dia.	mm(in.)		75(3)	
Swivel wheels dia.	mm(in.)		125(5)	
Net weight	kg(lb.)	72(158.4)	78(171.6)	85(187)