

Portable Spot Air Conditioner, -Industrial Class

- ▲ Elaborately designed and manufactured with advanced rotary sealed compressor, hydrophilic membrane inner thread and highly efficient heat transmitter and exchanger.
- ▲ Versatile spot cooling in virtually any place such as manufacturing production lines, injection molding, metal forming, outdoor events, or server rooms.
- ▲ Features sleek, compact design, easy to use.
- ▲ Zero installation - simply roll it in, plug and turn on.
- ▲ Two speed options provide custom-controlled cooling.
- ▲ **Over half a million units sold worldwide, 100,000 units working in Japan!**



i-Lift No			4010107
Model			PSAC-35
Cooling Capacity	Rating conditions 95°F at 60% RH	Btu/h	12000
Electrical Characteristics	Voltage Requirement	V	1 Phase 115
	Total Power Consumption	KW	1.4
	Current Consumption (Max.)	A	12.5
	Min.-Max. Voltage	V	105-127
Fans	Motor Output-high/low	KW	0.22/0.18
Evaporator	Fans Type		Centrifugal
	Max. Air Flow-high/low	CFM	600/450
	Max. External Static Pressure	Mpa	1
Condenser	Fans Type		Centrifugal
	Max. Air Flow-high/low	CFM	1000/800
	Max. External Static Pressure	Mpa	4
Compressor	Type		Hermetic rotary
	Output	KW	0.9
Refrigerant	Type		R410A
Dimensions	WxDxH	inch	23.2x18.9x38.8
Net Weight/Gross Weight		lbs	136/154
Power Cord	Gauge	AWG	14
	Length	inch	98.4
Condensate Tank Capacity		gal	3.9
Operating Conditions	Min.-Max.(50%-40% RH)		64-109°F 60%-40%RH
Max.Sound Level		dB(A)	65



PSAC-35