

Semi-Electric Stacker PYJ series

- ▲ Ergonomic design with handle for easy pulling and pushing the stacker.
- ▲ Straddle legs and adjustable forks for different pallets.
- ▲ Strong brake castor for safety.
- ▲ Special frame design for heavy load 1000kg and 1500kg.
- ▲ Maintenance free battery.



PYJ1025

i-Lift No.		1550301	1550302	1550303	1550304
Model		PYJ1025	PYJ1030	PYJ1525	PYJ1530
Capacity	(kg) (lb.)	1000(2200)		1500(3300)	
Load Center	(mm) (in.)	400(15.7)			
Lifting Height	(mm) (in.)	75-2500 (3-100)	75-3000 (3-118)	75-2500 (3-100)	75-3000 (3-118)
Fork Length	(mm) (in.)	915(36)			
Min. outside turning radius	(mm) (in.)	2200(86.6)		2300(90.6)	
Outside Width Between Legs	(mm) (in.)	1080-1360(42.5-53.5)			
Inside Width Between Legs	(mm) (in.)	960-1240(37.8-48.8)			
Outside Width Between Forks	(mm) (in.)	210-800(8.3-31.5)			
Inside Width Between Forks	(mm) (in.)	10-600(0.4-23.6)			
Max.Lifting Speed With Full Loading	(m/min)	≥ 3.6			
Lower Speed		Controllable			
Lifting Motor	(W/V)	1600/12			
Battery	(Ah/V)	120/12			
Charger		220V/12V			
Overall Length	(mm) (in.)	1550(61)			
Overall Width	(mm) (in.)	1080-1360(42.5-53.5)			
Overall Height	(mm) (in.)	1770(69.7)	2020(79.5)	1770(69.7)	2020(79.5)
Load Wheel Diameter	(mm) (in.)	100(4)			
Steering Wheel Diameter	(mm) (in.)	200(8)			
Net Weight	(kg) (lb.)	440(968)	470(1037)	465(1023)	490(1078)