





Self-Elevating Semi-Electric Stacker SDYG

- Double linkae cylinder assembly.
- ▲ both fork and frame can lift or be fixed.





SDYG0511

| i-Lift No. | | 1551601 | 1551602 |
|-------------------------------------|-----------|-----------------------|-------------|
| Model | | SDYG0511 | SDYG0513 |
| Rated Capacity | kg(lb.) | 500(1100) | |
| Load Center | (mm)(in.) | 400(15.7) | |
| Max. Fork Height | (mm)(in.) | 1100(44) | 1300(51.2) |
| Min. Fork Height | (mm)(in.) | 90(3.5) | |
| Fork Length | (mm)(in.) | 1150(45.3) | |
| Overall Length | (mm)(in.) | 1600(63) | |
| Overall Width | (mm)(in.) | 790(31.1) | |
| Over Height | (mm)(in.) | 1400(55.1) | 1600(63) |
| Whole height(after tape file shelf) | (mm)(in.) | 2700(106.3) | 2900(114.2) |
| Turn Radius | (mm)(in.) | 1100(44) | 1120(44.1) |
| Fork Overall Width | (mm)(in.) | 535(21) | |
| Wheels Base | (mm)(in.) | 860(33.9) | |
| Front Load Wheel | (mm)(in.) | Nylon Φ70x60(2.6x2.4) | |
| Rear Steering Wheel | (mm)(in.) | Nylon Φ100x50(4x2) | |
| Balance Wheel | (mm)(in.) | Nylon Φ40x26(1.6x1) | |
| Training Wheel | (mm)(in.) | Nylon Φ30x26(1.2x1) | |
| Lifting Speed (Without load) | (mm/s) | 110 | |
| Lifting Speed (With load) | (mm/s) | 80 | |
| Lowering Speed (Without load) | (mm/s) | 80 | |
| Lowering Speed (With load) | (mm/s) | 80 | |
| Motors Lifting | (Kw) | 12V0.8 | |
| Battery Capacity | (V/Ah) | 12/33 | |
| Battery Weight | (kg)(lb.) | 10(22) | |
| Net Weight | (kg)(lb.) | 197(433.4) | 219(481.8) |