

Hand Pallet Truck TX series

One of best selling in the world.

▲ Reliable hydraulic pump:

German made seal kits afford hydraulic pump.

Unique technology on this pump, descending speed is of the load.

▲ Bushings in key points:

Longer life span and easily reparable.

▲ Easy pallet entry and exit:

Fork tip and tapered mounting bracket design for entry roller, provide protection for the roller itself and the load wheel, it is easier for entry and exit from pallet.

▲ Durable frame by heavy duty design:

Heavy-duty design with high quality steel plate and sturdy continuous welds thoughout.

▲ Conforms to EN1757-2.



i-Lift No.		1112001	1112002	1112003	1112004
Model		TX20S	TX20L	TX25S	TX25L
Capacity	kg(lb.)	2000(4400) 2500(5500)		()	
Max. Fork Height	mm(in.)	205 or 195(8.1 or7.7)			
Min. Fork Height	mm(in.)	85 or 75(3.3 or 3)			
Fork Length	mm(in.)	1150(45.3)	1220(48)	1150(45.3)	1220(48)
Width Overall Forks	mm(in.)	530(20.9)	685(27)	530(20.9)	685(27)
Individual Fork Width	mm(in.)	150(6)			
Front Load Roller	mm(in.)	Ф80×60 or Ф70×60(Ф3×2.4 or Ф3×2.4) ,Nylon,Polyurethane			
Steering Whee	mm(in.)	Ф200 or Ф180(Ф8 or Ф7) ,Nylon,Polyurethane,Rubber			
Net Weight	kg(lb.)	72(158.4)	77(169.4)	76(167.2)	79(173.8

Special fork size available.

Optional Backrest is available.