

Mini Walkie Pallet Truck/Li-Ion WPT series

- ▲ Solid metal shields not only protect the drive system, but also protect the operator's feet from injury.
- ▲ Bucher power pack with IP67 motor.
- ▲ Ergonomic & Smart Tilter design, integrated PIN code panel with LCD display for smart control and operation.
- ▲ The turtle speed switch on the handle makes low speed control more precise.
- ▲ One step exchange Lithium-ion battery, high reliable, standard 24V/25AH, option 24V/30AH
- ▲ 2.5h Quick charging(24V/10A charger), 4h long working time.
- ▲ Quiet operation, Curtis control specially works in narrow aisle.
- ▲ 72 units can be loaded in one 20 feet container.



WPT15

i-lift No.		1115101	1115102	1115103
Model		WPT15	WPT18	WPT20
Drive unit		Electric		
Operator type		Walkie		
Capacity	kg(lb.)	1500(3300)	1800(3960)	2000(4400)
Load center	mm(in.)	600(23.6)		
Wheelbase	mm(in.)	1220(48)		
Wheel material (Driving/balance/front wheel)		PU		
Wheel number (Driving/balance/front wheel)		1/0/4		
Driving wheel size	mm(in.)	Φ210x70(8.3x2.8)		
Front wheel size	mm(in.)	Φ80x70(3.1x2.8)		
Min. fork height	mm(in.)	85(3.3)		
Max. fork height	mm(in.)	190(7.5)		
Max.lifting height	mm(in.)	105(4.1)	110(4.3)	110(4.3)
Outside width between forks	mm(in.)	560/680(22/26.8)		
Inside width between forks	mm(in.)	240/360(9.5/14.2)		
Fork length	mm(in.)	1150/1220(45.3/48)		
Fork width	mm(in.)	160(6.3)		
Fork thickness	mm(in.)	50(2)		
Overall length	mm(in.)	1540(60.6)		
Overall width	mm(in.)	560/680(22/26.8)		
Overall height(with/without handle)	mm(in.)	1250/560(49.2/22)		
Turning radius	mm(in.)	1350(53)		
Travel speed,with load /without load	km/h	4.5		
Max.gradeability,with load/without load	%	3/5		
Service brake		Electromagnetic brake		
Drive motor	kw	DC 0.75		DC 0.85
Lift motor	kw	DC 0.5		
Battery voltage/capacity	V/Ah	24V/25Ah		48V/15Ah (25Ah&30Ah)
Battery weight	kg(lb.)	5(11)		6(13.2)
Controller		Curtis		
Truck weight	kg(lb.)	148(325.6)	155(341)	160(352)