

Mobile Weighing Cart ZF / XL series

- ▲ High accuracy with fixed load cell mounting.
- ▲ High level of water and humidity resistance.
- ▲ Long term reliability from a single circuit board with any extra connectors.
- ▲ Lower power consumption, auto shut off: 4 AA new batteries can last up to one year when weighing 10 pallets per day.
- ▲ Summation of weights with sequence number.Auto tare.
- ▲ Features weighing accuracy $\pm 2\text{kg}$ in 2000kg. 1kg graduation.
- ▲ Plus model for 0.5kg graduation is available for special order.
- ▲ Optional thermal printer integrated with the housing.

ZF/ZFP series

- ▲ Small and compact electronics specially developed for mobile weighing.
- ▲ Robust housing protects against impact and vibration.

XL/XLP series

- ▲ Extra-large digital display 27.6mm height.
- ▲ Steel display protection for shipping and operations.



XL20L
without printer



ZF20S
without printer



ZFP20S
with printer

| i-Lift No. | | 1210301 | 1210302 | 1210303 | 1210304 | 1211901 | 1211902 |
|---------------------|---------|-------------------------|------------|--------------|-------------|-----------|--------------|
| Model | | ZF20S | ZF20L | ZFP20S | ZFP20L | XL20L | XLP20L |
| Capacity | kg(lb.) | 2300 (5000) | | | | | |
| Printer | | -- | | with printer | | -- | with printer |
| Max. Fork Height | mm(in.) | 205 or 195 (8.1 or 7.7) | | | | | |
| Min. Fork Height | mm(in.) | 85 or 75(3.3 or 3) | | | | | |
| Fork Length | mm(in.) | 1150 (45.3) | | | | | |
| Fork Width | mm(in.) | 180 (7) | | | | | |
| Width Overall Forks | mm(in.) | 555 (21.9) | 690 (27.2) | 555 (21.9) | 690 (27.2) | | |
| Net Weight | kg(lb.) | 117 (257.4) | 120 (264) | 118 (259.6) | 121 (266.2) | 125 (275) | 126 (277.2) |